



KWC

KWC
AVA 2.0



THE EPITOME OF SIMPLICITY

Unique flat lever, elegant soft-cube design, ultrasleek silhouette – those with an eye for the essential will recognize the clear statement in the new KWC AVA 2.0. Whoever lives here knows exactly what they want from life – and from their bathroom: stylish confidence, simple elegance, excellent quality, and functionality so perfect that you barely even notice it.



Form Meets Function

The unique flat lever of KWC AVA 2.0 is symbolic of its perfect synthesis of modern architecture and contemporary lifestyle.

Trend-setting Innovation

Perfectly adjusted water stream: the PERLATOR® HONEYCOMB® SSR aerator allows the direction of the water stream to be adjusted to suit the washbasin.



TREPLUS



The Innovative Platform


The new KWC AVA 2.0 shines bright, mostly with inner values: TREPLUS is the innovative new platform that forms the basis for the entire faucet. The KWC cartridge M 35 OP is the key component with its millionfold proven ceramic disc technology: as hard as diamond and resistant to calcium, ceramic discs permit light and easy use, and incomparable longevity.

- **Intuitive, simple maintenance**
- **Modern, slim design**
- **Fast, secure installation**
- **Complies with and exceeds national and international standards in terms of safety, drinking water hygiene, and health**
- **Exquisite quality of material and workmanship of individual parts**

Cartridge


The new KWC cartridge takes comfort to a new level: operation feels even more pleasant and natural. In addition, it permits an extremely precise and individual setting of water quantity and temperature. Even for the installer, the handling has never been so simple and comfortable.

KWC +




CoolFix

Intelligent and efficient resource usage: With CoolFix, when the lever is in the center – the most common position – the water runs cold. Only when the lever is turned to the left, the water runs warm.



EcoProtect

For economical water consumption and responsible use of resources: EcoProtect represents our commitment to promoting a sustainable lifestyle.




HealthProtect

Better hygiene and unchanged water quality: HealthProtect highlights the strict standards we set ourselves to ensure that our faucets do not affect the taste and smell of your water – that is why we use high-quality materials (metals, plastics) that are ideally suited for contact with water.




GlacierFinish

Robust surfaces and high-quality craftsmanship: GlacierFinish is equipped with durable surfaces that are exceptionally robust and feature an attractive polished shine that you can enjoy for years to come.




UniqueLever

Innovative lever designs that allow for natural and intuitive use: UniqueLever features innovative KWC design – elegance and precision that you can not only see, but also feel every day.




QuickInstallation

Hassle-free positioning and fastening of the threaded connection for quick and easy installation: the locking nut is screwed into place by hand to hold the faucet in position using QuickInstallation, before it is fixed in place via the two locking screws.




OptimalSpace

Practical yet elegant ergonomic design: OptimalSpace features long, tall spouts that provide ample space for washing and/or working.



TouchProtect

Safe to use: An insulated hot water guidance system with a “double skin” principle means the body of the faucet or the pull-out spray can become warm but never hot. In this way, TouchProtect intelligently prevents scalding.



SkinProtect

Effective protection against scalding: With SkinProtect, your faucet will only supply you with water hotter than 38°C when you press the safety button on the temperature controller. If the cold water is shut off, the faucet automatically shuts off the hot water immediately.





**Basin**


Lever mixer

- EcoProtect - water-saving device
- Fixed spout
 - Neoperl® Perlator® SSR, swivelling jet regulator
- Flow rate and temperature continuously variable
- QuickInstallation - Fastening via threaded connection with locking screws

12.468.041.000FL all chrome A 105 with pop-up valve

12.468.051.000FL all chrome A 105 without pop-up valve

12.468.641.000FL all chrome A 105 with Push Open

**Basin**

Lever mixer

- CoolFix - Cold water flow with a centered lever
- EcoProtect - water-saving device
- Fixed spout
 - Neoperl® Perlator® SSR, swivelling jet regulator
- Flow rate and temperature continuously variable
- QuickInstallation - Fastening via threaded connection with locking screws

12.468.031.000FL all chrome A 105 with pop-up valve

12.468.071.000FL all chrome A 105 without pop-up valve

12.468.631.000FL all chrome A 105 with Push Open

**Basin**


Lever mixer

- EcoProtect - water-saving device
- Fixed spout
 - Neoperl® Perlator® SSR, swivelling jet regulator
- Flow rate and temperature continuously variable
- QuickInstallation - Fastening via threaded connection with locking screws

12.468.042.000FL all chrome A 125 with pop-up valve

12.468.052.000FL all chrome A 125 without pop-up valve

12.468.642.000FL all chrome A 125 with Push Open

**Basin**

Lever mixer

- CoolFix - Cold water flow with a centered lever
- EcoProtect - water-saving device
- Fixed spout
 - Neoperl® Perlator® SSR, swivelling jet regulator
- Flow rate and temperature continuously variable
- QuickInstallation - Fastening via threaded connection with locking screws

12.468.032.000FL all chrome A 125 with pop-up valve

12.468.072.000FL all chrome A 125 without pop-up valve

12.468.632.000FL all chrome A 125 with Push Open

**Basin**

Lever mixer

- EcoProtect - water-saving device
- Fixed spout
 - Neoperl® Perlator® SSR, swivelling jet regulator
- OptimalSpace - ample space for washing or working
- Flow rate and temperature continuously variable
- QuickInstallation - Fastening via threaded connection with locking screws

12.468.043.000FL all chrome A 145 with pop-up valve

12.468.053.000FL all chrome A 145 without pop-up valve

12.468.643.000FL all chrome A 145 with Push Open

**Basin**

Lever mixer

- CoolFix - Cold water flow with a centered lever
- EcoProtect - water-saving device
- Fixed spout
 - Neoperl® Perlator® SSR, swivelling jet regulator
- OptimalSpace - ample space for washing or working
- Flow rate and temperature continuously variable
- QuickInstallation - Fastening via threaded connection with locking screws

12.468.033.000FL all chrome A 145 with pop-up valve

12.468.073.000FL all chrome A 145 without pop-up valve

12.468.633.000FL all chrome A 145 with Push Open


**Basin**

Lever mixer

- For top-mounted basins
- EcoProtect - water-saving device
- Fixed spout
 - Neoperl® Perlator® SSR, swivelling jet regulator
- OptimalSpace - ample space for washing or working
- Flow rate and temperature continuously variable
- QuickInstallation - Fastening via threaded connection with locking screws

12.468.093.000FL all chrome A 185
without pop-up valve

12.468.663.000FL all chrome A 185
with Push Open

**Basin**


Lever mixer

- Lever installation only possible on the right side
- EcoProtect - water-saving device
- Swivel spout 120°
 - Neoperl® Perlator® SSR, swivelling jet regulator
- OptimalSpace - ample space for washing or working
- Flow rate and temperature continuously variable
- QuickInstallation - Fastening via threaded connection with locking screws

12.468.131.000FL all chrome A 150
with pop-up valve

12.468.141.000FL all chrome A 150
without pop-up valve

12.468.651.000FL all chrome A 150
with Push Open


**Basin**

Trim kit Lever mixer

- Fixed spout
 - Neoperl® Perlator® SSR, swivelling jet regulator
- OptimalSpace - ample space for washing or working
- Flow rate and temperature continuously variable
- To be ordered separately:
 - Unit for concealed installation ½" 39.001.402.000

11.462.063.000 all chrome A 175

11.462.064.000 all chrome A 225


**Basin**

Trim kit Lever mixer

- Fixed spout
 - Neoperl® Perlator® SSR, swivelling jet regulator
- OptimalSpace - ample space for washing or working
- Flow rate and temperature continuously variable
- To be ordered separately:
 - Unit for concealed installation ½" 39.001.402.000

11.462.033.000 all chrome A 175


11.462.034.000 all chrome A 225

**Tub**

Lever mixer

- For freestanding tub
- Fixed spout
 - Neoperl® Perlator® laminar
- Flow rate and temperature continuously variable
- Temperature limitation
- Scope of delivery:
 - Hand shower KWC FIT-X slim 26.000.103.000
 - Shower hose 1500 mm, metal
- To be ordered separately:
 - Unit for concealed installation 39.000.602.931


20.461.093.000 all chrome A 250

**Bidet**

Lever mixer

- Fixed spout
 - ball joint aerator Neoperl® Caché®
- Flow rate and temperature continuously variable
- QuickInstallation - Fastening via threaded connection with locking screws

13.461.041.000FL all chrome A 110
with pop-up valve




Tub

Lever mixer

- TouchProtect - anti-scald protection thanks to the "double skin" principle
- Intrinsicly safe against backflow
- Fixed spout
 - Neoperl® Perlator® laminar
- Flow rate and temperature continuously variable
- Temperature limitation
- Wall connections 1/2" x 3/4", without shut-off valve eccentric 10 mm

20.462.483.000

all chrome AD 150 +/- 20 mm, A 185 without hand shower, hose and bracket




Shower

Lever mixer

- TouchProtect - anti-scald protection thanks to the "double skin" principle
- Intrinsicly safe against backflow
- Flow rate and temperature continuously variable
- Temperature limitation
- Wall connections 1/2" x 3/4", without shut-off valve eccentric 10 mm

21.462.480.000

all chrome AD 150 +/- 20 mm without hand shower and hose




Tub

Thermostatic mixer design

- EcoProtect - water-saving device
- TouchProtect - anti-scald protection thanks to the "double skin" principle
- SkinProtect - Safety stop prevents scalding
- Turning handle to control flow and for diverter
- Intrinsicly safe against backflow
- Fixed spout
 - Neoperl® Cascade®
- Thermostatic precision control unit
- constant water temperature (even when mains pressure fluctuates)
- fast response
- Wall connections 1/2" x 3/4", without shut-off valve eccentric 10 mm

26.009.733.000

all chrome AD 150 +/- 20 mm, A 180 without hand shower, hose and bracket




Shower

Thermostatic mixer design

- EcoProtect - water-saving device
- TouchProtect - anti-scald protection thanks to the "double skin" principle
- SkinProtect - Safety stop prevents scalding
- Turning handle to control flow
- Intrinsicly safe against backflow
- Thermostatic precision control unit
- constant water temperature (even when mains pressure fluctuates)
- fast response
- Wall connections 1/2" x 3/4", without shut-off valve eccentric 10 mm

26.009.130.000

all chrome AD 150 +/- 20 mm without hand shower and hose




Shower

Lever mixer

- Intrinsicly safe against backflow
- Flow rate and temperature continuously variable
- Temperature limitation
- Wall connections 1/2" x 3/4", without shut-off valve eccentric 10 mm

21.462.330.000


all chrome AD 150 +/- 20 mm without hand shower and hose

**Tub**


- Trim kit with function unit
- Outflow top and below
 - Turning handle for diverter
 - Flow rate and temperature continuously variable
 - Scope of delivery:
 - Function unit, lever, cap, sleeve, cover plate, holder for escutcheon, diverter
 - Fastening of the cover plate without screws
 - To be ordered separately:
 - Unit for concealed installation KWC BLUEBOX®
 - 1/2", without shut-off valve, 39.999.900.931
 - 3/4" (1/2"), with shut-off valve, 39.999.910.931
 - 3/4", with shut-off valve 39.999.930.931

20.464.500.000 all chrome**20.464.510.000** all chrome with vacuum breaker**Shower**


- Trim kit with function unit
- Outflow top or below
 - Flow rate and temperature continuously variable
 - Scope of delivery:
 - Function unit, lever, cap, sleeve, cover plate, holder for escutcheon
 - Fastening of the cover plate without screws
 - To be ordered separately:
 - Unit for concealed installation KWC BLUEBOX®
 - 1/2", without shut-off valve, 39.999.900.931
 - 3/4" (1/2"), with shut-off valve, 39.999.910.931
 - 3/4", with shut-off valve 39.999.930.931

21.464.500.000 all chrome**Tub**

- Trim kit with thermostatic function unit design
- Outflow top and below
 - SkinProtect - Safety stop prevents scalding
 - Turning handle to control flow and for diverter
 - Intrinsicly safe against backflow
 - Scope of delivery:
 - Function unit, temperature lever, sleeve, cover plate, holder for escutcheon handle to control flow and for diverter
 - Fastening of the cover plate without screws
 - To be ordered separately:
 - Unit for concealed installation KWC BLUEBOX®
 - 1/2", without shut-off valve, 39.999.900.931
 - 3/4" (1/2"), with shut-off valve, 39.999.910.931
 - 3/4", with shut-off valve 39.999.930.931

20.004.801.000 all chrome**20.004.811.000** all chrome with vacuum breaker**Shower**

- Trim kit with thermostatic function unit design
- Outflow top or below
 - SkinProtect - Safety stop prevents scalding
 - Turning handle to control flow
 - Intrinsicly safe against backflow
 - Scope of delivery:
 - Function unit, temperature lever, sleeve, cover plate, holder for escutcheon handle to control flow
 - Fastening of the cover plate without screws
 - To be ordered separately:
 - Unit for concealed installation KWC BLUEBOX®
 - 1/2", without shut-off valve, 39.999.900.931
 - 3/4" (1/2"), with shut-off valve, 39.999.910.931
 - 3/4", with shut-off valve 39.999.930.931

21.004.801.000 all chrome**Bathtub spout design**

- Fixed spout
- Neoperl® Cascade®
- Connecting thread 1/2"

26.008.033.000 all chrome A 200**KWC Sliding wall bar FIT design**

- KWC ball joint bracket, elevation adjustment lockable
- Tube diameter 18 mm

26.000.504.000 all chrome L 612**26.000.505.000** all chrome L 1100

