



DESIGNPREIS  
2006  
NOMINEE



reddot design award  
winner 2005

KWC-No.	Finish
<b>10.121.103.000FL</b>	all chrome
A 225, flexible connection hoses, mains receiver	
<b>10.121.103.700FL</b>	stainless steel
A 225, flexible connection hoses, mains receiver	



product  
design  
award

2006

## Kitchen with LEDShine

LUMINAQUA®  
Advanced Light Technology

EDELSTAHL  
STAINLESS STEEL



### Lever mixer

- Lever installation possible on the right or left side
- TouchProtect - anti-scald protection thanks to the "double skin" principle
- Pull-out aerator covered
  - Neoperl® Caché®
  - integrated ON/OFF push-button with automatic shut-off after 45 minutes
  - up to 600 mm pull-out length
  - hose surface to fit faucet surface
- Hose guide, swivelling 320°
- EasyLock - a pull-out spray that easily slides back into place
- OptimalSpace - ample space for washing or working
- KWC cartridge M 35
  - with ceramic discs
  - flow rate and temperature continuously variable
- Flexible connection hoses 3/8"
- Fastening by means of threaded sleeve M33 x 1.5
- Mounting hole size ø35 mm
- Scope of delivery:
  - Mains receiver 100-240 V / operating voltage 6.75 V / cable length 1100 mm

Flow rate 10 l/min (3 bar)  
Acoustic group I

Subject to technical, range and model changes. Dimensions in mm.