



KWC-No.	Finish
10.201.242.127FL	decor steel
A 215, flexible connection hoses, mains receiver	

Kitchen with LEDShine, touch light PRO

IntelligentControl - electronic control

- touch light PRO technology
- touch'n'flow 1-2-3
- 3 preset temperatures and flow rates
- Position of control unit only possible on the right side
- gap between wall and centre of mounting hole min. 42 mm
- TouchProtect - anti-scald protection thanks to the "double skin" principle
- Microprocessor-control
 - touch'n'flow 1: cold water, 50% flow rate can be individually adjusted and saved
 - touch'n'flow 2: warm water, 50% flow rate can be individually adjusted and saved
 - touch'n'flow 3: hot water, 50% flow rate can be individually adjusted and saved
 - with cleaning programme
 - duration of water flow - safety indication: switch off automatically after 10 minutes
 - temperature limit can be adjusted
 - hot water disinfection (5 minutes) can be adjusted
 - can be restored to factory settings
- Covered pull-out spray
 - ergonomic spout alignment, shape and handling
 - SprayClean - easy to clean and actively prevents limescale buildup
 - Neoperl® Cascade®
 - PowerClean - needle spray mode, with automatic diverter reset
 - integrated ON/OFF push-button with automatic shut-off after 30 minutes
 - up to 500 mm pull-out length
 - hose surface to fit faucet surface
- SwivelStop - hose guide, swivelling 270°, limitable to 120°
- EasyLock - a pull-out spray that easily slides back into place
- OptimalSpace - ample space for washing or working
- touch light PRO control unit, maintenance-free
 - up-to-date microprocessor and drive technology

- tried-and-tested valve technology
- incl. installation materials
- designed for wired connection to 1 operating unit (standard)
- Flexible connection hoses 3/8"
- Fastening by means of threaded sleeve M33 x 1.5
- Mounting hole size ø35 mm
- Scope of delivery:
 - Mains receiver 100-240 V / operating voltage 15 V / cable length 900 mm
- To be ordered separately (optional or if necessary):
 - Extension set 1500 mm Z.536.352, comprising: stainless steel hose 1500 mm, 3/8" x 3/8", double nipple, sealing material

Flow rate normal spray 9 l/min (3 bar)

Flow rate needle spray 10 l/min (3 bar)

Acoustic group I

Subject to technical, range and model changes. Dimensions in mm.