
TECHNICAL DATA SHEET



Range: Pack for accessibility Ref: 60063 - Presto pack comfort for shower





> Function:

- . This PRESTO Comfort shower pack consists of an extra-flat shower tray (with siphon included), a thermostatic wall-mounted mixer, a corner bar with a vertical bar,
- a hanging seat, and a complete shower bar, allows a quick and easy compliance of a bathroom for people with reduced mobility
 The extra-flat tray makes it easier for wheelchair users to reach comfort and safety for the user.
- The thermostatic mixing valve allows a precise adjustment of the desired temperature, a comfort particularly appreciated by the users and caregivers.

> Composition:

- Extra-flat shower tray 900 x 900 mm with floor drain ref. 60201
 Thermostatic wall-mounted mixer with ergonomic control ref.75640
 Corner bar with vertical bar in aluminum ABS antibacterial sheath ref. 60724
 Hanging shower seat in nylon sheathed aluminum ref.60420
- Shower rail complete with adjustable, flexible support and hand shower ref.60260

> Flow rate:

- 17 L / min at 3 bar
- > Material and finish color:

· Chrome-plated solid brass body

> Standards / Approvals:

- Nickel-Chrome surface treatment according to NF EN12540
 Resistance to neutral salt spray (NSS): 200 h according to NF ISO 9227
 Certificate of Sanitary Compliance ACS

> Recommended pressure of use:

- 1 to 5 bar
- > Hydraulic power supply:
 - G 3/4 "(20x27) rear entries on turn nuts with NF non-return valves

> Thermal resistance:

This valve withstands a temperature of 75 ° C in the context of thermal shocks to eradicate legionella as recommended by the French decree of November 30
 2005 for fixed installations for heating and hot water supply of residential buildings, work premises or premises receiving from the public

> Security:

- Anti-scalding safety: instant stop of hot water in case of cold water break
 Maximum delivered temperature: preset to 38 °

> Ergonomics:

- 50 mm ergonomic handle
- > Delivered with:
 - · 2 sieve filter seals
 - 2 eccentric fittings MM G 1/2 "(15x21) G3 / 4" (20x27) · 2 rosettes

